

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Original) An apparatus for air-cooling and tempering a glass sheet,  
comprising:

a conveying means installed to be operable from a forming zone to a cooling area and  
to convey a glass sheet in a high temperature state,

a plurality of upper blowing members provided in parallel along a conveying direction  
of glass sheet above the conveying means in the cooling area,

a plurality of lower blowing members provided in parallel along a conveying direction  
of glass sheet under the conveying means in the cooling area,

a plurality of air-supply boxes provided in each of the upper and lower blowing  
members for controlling blow/stop operations of cooling air from each of the blowing  
members, and

an air-supply source connected to these air-supply boxes,

wherein each of the air-supply boxes comprises a cylindrical damper having a  
perforated hole provided at its side, a casing for rotatably accommodating the damper and for  
forming an air channel only when the damper is at a predetermined rotational position, and a  
slide bearing provided in a space between the damper and the casing, wherein the cooling air  
supplied from the air-supply source can be supplied to the upper and/or lower blowing  
members through air channels by adjusting the rotational position of the damper.

Claim 2 (Original) The apparatus for air-cooling and tempering a glass sheet  
according to Claim 1, further comprising a control means for controlling the rotational  
position of a damper so that it

(a) stops cooling air to be blown from all of the upper and lower blowing members in the cooling area in the initial state,

(b) blows the cooling air from all of the upper and lower blowing members when the substantially whole of a conveyed glass sheet is entered in the cooling area, and

(c) sequentially stops the cooling air blown from the upper and lower blowing members located behind the glass sheet in response to the conveyance position of the glass sheet after the last glass sheet in the cooling area is passed.

Claim 3 (Currently Amended) The apparatus for air-cooling and tempering a glass sheet according to Claim 1 ~~or 2~~, wherein an upper and/or lower blowing member comprises an air-nozzle swingable in the conveying direction of glass sheet.

Claim 4 (Currently Amended) The apparatus for air-cooling and tempering a glass sheet according to Claims 1 ~~to 3~~, wherein the conveying means is a conveyor comprising a plurality of rollers disposed in parallel along the conveying direction of glass sheet.

Claim 5 (Original) The apparatus for air-cooling and tempering a glass sheet according to Claim 4, wherein the rollers move up and down according to the position of a glass sheet so that a curved glass sheet can be conveyed.

Claim 6 (Currently Amended) The apparatus for air-cooling and tempering a glass sheet according to ~~any one of Claims 1 to 5~~ Claim 1, wherein a plurality of dampers are connected via an Oldham's coupling.

Claim 7 (Currently Amended) The apparatus for air-cooling and tempering a glass sheet according to ~~any one of Claims 1 to 6~~ Claim 1, wherein the glass sheet is for a window glass of automobiles.

Claim 8 (Original) In a process for air-cooling and tempering a glass sheet comprising employing an apparatus for air-cooling and tempering a glass sheet, the apparatus comprising a conveying means installed to be operable from a forming zone to a cooling area and to convey a glass sheet in a high temperature state, a plurality of upper blowing members provided in parallel along a conveying direction of glass sheet above the conveying means in the cooling area, a plurality of lower blowing members provided in parallel along a conveying direction of glass sheet under the conveying means in the cooling area, a plurality of air-supply boxes provided in each of the upper and lower blowing members so as to control blow/stop of cooling-air from each of the blowing members, and an air-supply source connected to these air-supply boxes, the process being characterized by comprising:

(a) a step of stopping cooling air from all of the upper and lower blowing members in the cooling area in the initial state,

(b) a step of blowing the cooling air from all of the upper and lower blowing members when the substantially whole of a conveyed glass sheet is entered in the cooling area, and

(c) a step of sequentially stop the cooling air blown from the upper and lower blowing members located behind the glass sheet in response to the conveyance position of the glass sheet after the last glass sheet in the cooling area is passed.

Claim 9 (Original) The process for air-cooling and tempering a glass sheet according to Claim 8, wherein an upper and/or lower blowing member comprises an air-nozzle swingable in the conveying direction of glass sheet.

Claim 10 (Currently Amended) The process for air-cooling and tempering a glass sheet according to Claim 8 ~~or 9~~, wherein the conveying means is a conveyer comprising a plurality of rollers disposed along the conveying direction of glass sheets.

Claim 11 (Original) The process for air-cooling and tempering a glass sheet according to Claim 10, wherein the rollers move up and down according to the position of the glass sheet so that a curved glass sheet can be conveyed.

Claim 12 (Currently Amended) The process for air-cooling and tempering a glass sheet according to ~~any one of Claims 8 to 11~~ Claim 8, wherein a plurality of dampers are connected via an Oldham's coupling.

Claim 13 (Currently Amended) The apparatus for air-cooling and tempering a glass sheet according to ~~any one of Claims 8 to 12~~ Claim 8, wherein the glass sheet is for a window glass of automobiles.